



**PROJECT** \_\_\_\_\_

**TYPE** \_\_\_\_\_

**NOTES** \_\_\_\_\_

**QUANTITY** \_\_\_\_\_

**DATE** \_\_\_\_\_



Ceiling suspended luminaire made from aluminium; surface White Matt wet painted; matt texture; inclusive adjustable cable suspension max. 4000mm in Pure White; with COB (Chip on Board) technology for maximum efficiency; light colour 3000 K; CRI ≥ 90; beam angle 32°; degree of protection IP20; Class 3; ceiling base included; Loxone ready;

**General**

Ceiling \_\_\_\_\_  
 Suspended \_\_\_\_\_  
 White Matt \_\_\_\_\_  
 IP20 \_\_\_\_\_  
 Interior \_\_\_\_\_  
 450 lm \_\_\_\_\_

**LED**

3000 K \_\_\_\_\_  
 CRI ≥ 90 \_\_\_\_\_  
 L70 / 55000h \_\_\_\_\_  
 ≤ 2 SDCM (initial MacAdam) \_\_\_\_\_

**Optical**


beam angle 32° \_\_\_\_\_

**Electrical**

excl. driver \_\_\_\_\_  
 24 V \_\_\_\_\_  
 system 7.0 W \_\_\_\_\_  
 Class III \_\_\_\_\_  
 Standard \_\_\_\_\_

**Physical**

diameter 115 mm \_\_\_\_\_  
 height 235 mm \_\_\_\_\_  
 0.35 kg \_\_\_\_\_  
 cable length max. 2500 mm \_\_\_\_\_  
 base included \_\_\_\_\_



[‘28756LWW5’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.