




PROJECT _____

TYPE _____

NOTES _____

QUANTITY _____

DATE _____



Cylindrical ceiling suspended luminaire made from die-cast aluminium; surface White Matt; powder coated; matt texture; RAL 9010; with COB (Chip on Board) technology for maximum efficiency; 350 mA; light colour 3000 K; CRI ≥ 90; beam angle 75°; 24 V; degree of protection IP20; Class 3; ceiling base included; Loxone ready; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

General

Ceiling _____
 Suspended _____
 White Matt _____
 RAL 9010 ^a _____
 IP20 _____
 Interior _____
 565 lm _____

LED

3000 K _____
 CRI ≥ 90 _____
 L80 / 50000h _____

Optical

Wide _____
 beam angle 75° _____


Electrical

excl. driver _____
 24 V _____
 inset 6.0 W ^b _____
 Class III _____
 Standard _____

Physical

diameter 43 mm _____
 height 300 mm _____
 0.33 kg _____
 cable length 4000 mm _____
 base included _____

^a Colour may deviate slightly due to production conditions
^b Without electrical and optical losses



[26017LW5] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.