




PROJECT _____

TYPE _____

NOTES _____

QUANTITY _____

DATE _____



Cylindrical ceiling surface mounted downlight made from die-cast aluminium; surface White Matt; powder coated; matt texture; RAL 9010; with COB (Chip on Board) technology for maximum efficiency; light colour 3000 K; CRI ≥ 90; beam angle 30°; degree of protection IP20; Class 3; Loxone ready; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

General

Ceiling _____
 Surface _____
 White Matt _____
 RAL 9010 ^a _____
 IP20 _____
 Interior _____
 480 lm _____

LED

3000 K _____
 CRI ≥ 90 _____
 L80 / 55000h _____

Optical

Medium (standard) _____
 beam angle 30° _____


Electrical

excl. driver _____
 24 V _____
 system 7.0 W _____
 Class III _____
 Standard _____

Physical

diameter 70 mm _____
 height 85 mm _____
 0.19 kg _____

^a Colour may deviate slightly due to production conditions



[25825LWW5] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.