WEVER & DUCRÉ LIGHTING

BOX mini 1.0 Loxone

25815LBB3

PROJECT

TYPE

NOTES

QUANTITY

DATE



Squared ceiling surface mounted downlight made from die-cast aluminium; surface Black Matt; powder coated; matt texture; RAL 9011; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K; CRI ≥ 90; beam angle 30°; degree of protection IP20; Class 3; Loxone ready; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

LUMINAIRE

Ceiling
Surface
Black Matt
RAL 9011 [a]
IP20
Interior
470 lm

LED MODULE

2700 K
CRI ≥ 90
L80 / 55000h

OPTICAL

Medium (standard)
beam angle 30°


ELECTRICAL

Loxone
24 V
system 7.0 W
Class III

PHYSICAL

length 70 mm
width 70 mm
height 85 mm
0.25 kg

[a] Colour may deviate slightly due to production conditions



['25815LBB3'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com