




PROJECT

TYPE

NOTES

QUANTITY

DATE



Cylindrical ceiling suspended luminaire made from die-cast aluminium; surface White Matt; powder coated; matt texture; RAL 9010; inclusive adjustable cable suspension max. 4000mm in Pure White; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K; CRI ≥ 90; 24 V; degree of protection IP20; Class 3; Loxone ready; ceiling base included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

General

Ceiling _____
 Suspended _____
 White Matt _____
 RAL 9010 ^a _____
 IP20 _____
 Interior _____
 405 lm _____

LED

2700 K _____
 CRI ≥ 90 _____
 L80 / 55000h _____
 ≤ 2 SDCM (initial MacAdam) _____

Optical

Medium (standard) _____
 beam angle 36° _____


Electrical

excl. driver _____
 24 V _____
 system 6.0 W _____
 Class III _____
 Standard _____

Physical

diameter 67 mm _____
 height 300 mm _____
 0.76 kg _____
 cable length 4000 mm _____

^a Colour may deviate slightly due to production conditions



[‘22686LW3’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.