



**PROJECT**

---

**TYPE**

---

**NOTES**


---

**QUANTITY**

---

**DATE**

---



Cylindrical ceiling suspended luminaire made from die-cast aluminium; surface Champagne Brushed; inclusive adjustable cable suspension max. 4000mm in Signal Black; with COB (Chip on Board) technology for maximum efficiency; light colour 3000 K; CRI ≥ 90; 24 V; degree of protection IP20; Class 3; Loxone ready; ceiling base included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

**General**

Ceiling  
Suspended  
Champagne Brushed  
IP20  
Interior  
425 lm

**LED**

3000 K  
CRI ≥ 90  
L80 / 55000h  
≤ 2 SDCM (initial MacAdam)

**Optical**


Medium (standard)  
beam angle 36°

**Electrical**

excl. driver  
24 V  
system 6.0 W  
Class III  
Standard

**Physical**

diameter 67 mm  
height 300 mm  
0.76 kg  
cable length 4000 mm



[22686LM5] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.