




PROJECT

TYPE

NOTES

QUANTITY

DATE



Cylindrical ceiling suspended luminaire made from die-cast aluminium; surface Champagne Brushed; inclusive adjustable cable suspension max. 4000mm in Signal Black; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K; CRI ≥ 90; 24 V; degree of protection IP20; Class 3; Loxone ready; ceiling base included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

General

Ceiling
Suspended
Champagne Brushed
IP20
Interior
405 lm

LED

2700 K
CRI ≥ 90
L80 / 55000h
≤ 2 SDCM (initial MacAdam)

Optical


Medium (standard)
beam angle 36°

Electrical

excl. driver
24 V
system 6.0 W
Class III
Standard

Physical

diameter 67 mm
height 300 mm
0.76 kg
cable length 4000 mm



[22686LM3] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.