




PROJECT

TYPE

NOTES

QUANTITY

DATE



Cylindrical ceiling suspended luminaire made from die-cast aluminium; surface Aluminium Brushed; RAL 9006; inclusive adjustable cable suspension max. 4000mm in Signal Black; with COB (Chip on Board) technology for maximum efficiency; light colour 3000 K; CRI \geq 90; 24 V; degree of protection IP20; Class 3; Loxone ready; ceiling base included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

General

Ceiling _____
 Suspended _____
 Aluminium Brushed _____
 RAL 9006 ^a _____
 IP20 _____
 Interior _____
 425 lm _____

LED

3000 K _____
 CRI \geq 90 _____
 L80 / 55000h _____
 \leq 2 SDCM (initial MacAdam) _____

Optical

Medium (standard) _____
 beam angle 36° _____


Electrical

excl. driver _____
 24 V _____
 Class III _____
 Standard _____

Physical

diameter 67 mm _____
 height 200 mm _____
 0.62 kg _____
 cable length 4000 mm _____

^a Colour may deviate slightly due to production conditions



[22676LL5] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.