



**PROJECT**

---

**TYPE**

---

**NOTES**


---

**QUANTITY**

---

**DATE**

---



Cylindrical ceiling suspended luminaire made from die-cast aluminium; surface Gold Brushed; inclusive adjustable cable suspension max. 4000mm in Signal Black; with COB (Chip on Board) technology for maximum efficiency; light colour 3000 K; CRI  $\geq$  90; 24 V; degree of protection IP20; Class 3; Loxone ready; ceiling base included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

**General**

Ceiling \_\_\_\_\_  
 Suspended \_\_\_\_\_  
 Gold Brushed \_\_\_\_\_  
 IP20 \_\_\_\_\_  
 Interior \_\_\_\_\_  
 425 lm \_\_\_\_\_

**LED**

3000 K \_\_\_\_\_  
 CRI  $\geq$  90 \_\_\_\_\_  
 L80 / 55000h \_\_\_\_\_  
 $\leq$  2 SDCM (initial MacAdam) \_\_\_\_\_

**Optical**


Medium (standard) \_\_\_\_\_  
 beam angle 36° \_\_\_\_\_

**Electrical**

excl. driver \_\_\_\_\_  
 24 V \_\_\_\_\_  
 Class III \_\_\_\_\_  
 Standard \_\_\_\_\_

**Physical**

diameter 67 mm \_\_\_\_\_  
 height 200 mm \_\_\_\_\_  
 0.62 kg \_\_\_\_\_  
 cable length 4000 mm \_\_\_\_\_



[‘22676LG5’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.