WEVER & DUCRÉ LIGHTING

RAY SUSPENDED 2.0 Loxone

22676LB3

PROJECT


TYPE

NOTES


QUANTITY

DATE





Cylindrical ceiling suspended luminaire made from die-cast aluminium; surface Black Matt; powder coated; matt texture; RAL 9011; inclusive adjustable cable suspension max. 4000mm in Signal Black; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K; CRI ≥ 90; 24 V; degree of protection IP20; Class 3; Loxone ready; ceiling base included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



LUMINAIRE

Ceiling
Suspended
Black Matt
RAL 9011 [a]
IP20
Interior
405 lm

LED MODULE

2700 K
CRI ≥ 90
L80 / 55000h
≤ 2 SDCM (initial MacAdam)

OPTICAL

Medium (standard)
beam angle 36°

ELECTRICAL

Loxone
24 V
system 7.0 W
Class III

PHYSICAL

diameter 67 mm
height 200 mm
0.62 kg
cable length 4000 mm

[a] Colour may deviate slightly due to production conditions

['22676LB3'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com