



**PROJECT**

---

**TYPE**

---

**NOTES**

---

**QUANTITY**


---

**DATE**

---



Ceiling suspended luminaire; italian hand blown white opal glass; mounting made from aluminium in Black Matt; powder coated; matt texture; inclusive adjustable cable suspension max. 2500mm; lamp socket G9; lamp type QT14; max. 5W; 220 - 240 V; degree of protection IP20; Class 1; lamp not included;



**General**

Ceiling  
Suspended  
Black Matt + White Opal Glass  
No matching RAL  
IP20  
Interior  
260 lm

**LED**

lamp QT14  
socket G9  
max. per socket 5.0 W  
3000 K  
CRI ≥ 80  
≤ 6 SDCM (initial MacAdam)

**Optical**

Opal  
CIE flux code: 26 51 76 60 87

**Electrical**

220 - 240 V  
inset 3.0 W <sup>a</sup>  
Class I  
Standard

**Physical**


diameter 125 mm  
height 135 mm  
0.5 kg  
cable length 2500 mm

**datasheet.quicksum.material**

Glass

<sup>a</sup> Without electrical and optical losses

**LIGHT DISTRIBUTION**



[‘2521G0WB0’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.

2521G0WB0



## LAMPS

### QT14 LED Lamp

Type	Colour	Voltage	Ø·H (MM)	Item number
2700K   G9			19·49	9010G803
3000K   G9			19·49	9010G805