WEVER & DUCRÉ LIGHTING

LECA 1.0 Loxone

18816LW3

PROJECT


TYPE

NOTES


QUANTITY

DATE





Ceiling recessed spotlight made from die-cast aluminium with round base; surface White Matt; powder coated, matt texture; RAL 9010; installation without tools using wire springs; suitable for ceiling thickness of 4-26 mm; recessed depth 68mm; with COB (Chip on Board) technology for maximum efficiency; 350mA; light colour 2700 K; CRI ≥ 90; beam angle 31°; spotlight head 350° rotatable and 90° tiltable; degree of protection IP20; Class 3; IC rated; Loxone ready; optional optical accessories available; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



LUMINAIRE

Ceiling
Recessed
tilt max 90 °
rotation 350 °
White Matt
RAL 9010 [a]
IP20
IC rated
Interior
585 lm

LED MODULE

2700 K
CRI ≥ 90
L80 / 50000 h

OPTICAL

Medium (standard)
beam angle 31°

ELECTRICAL

Loxone
24 V
Class III

PHYSICAL

diameter 60 mm
height 73 mm
0.28 kg
wire springs

CUTOUT

diameter 40-41 mm
min. ceiling thickness 4 mm
max. ceiling thickness 26 mm
recessed depth 68 mm

[a] Colour may deviate slightly due to production conditions

LECA 1.0 Loxone

18816LW3

OPTICAL ACCESSORIES

HONEYCOMB LOUVRE FOR LOXONE

TYPE	COLOUR	VOLTAGE	Ø (MM)	ITEM NUMBER
	Black		29	91523LB0

['18816LW3'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.

© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com