WEVER & DUCRÉ LIGHTING

CENO 1.0 Loxone

17616LB3

PROJECT


TYPE

NOTES


QUANTITY

DATE





Ceiling recessed spotlight made from die-cast aluminium with round base; surface Black Matt; powder coated, matt texture; RAL 9011; inner ring black; installation without tools using blade springs; recessed depth 85mm; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K; ≤ 2 SDCM (initial MacAdam); CRI ≥ 90; beam angle 31°; 350° rotatable and 90° tiltable; degree of protection IP20; Class 3; IC rated; Loxone ready; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



LUMINAIRE

Ceiling
Semi-Recessed
tilt max 90 °
rotation 350 °
Black Matt
RAL 9011 [a]
IP20
IC rated
Interior
500 lm

LED MODULE

2700 K
CRI ≥ 90
L70 / 55000h
≤ 2 SDCM (initial MacAdam)

OPTICAL

Medium (standard)
beam angle 31°

ELECTRICAL

Loxone
24 V
Class III

PHYSICAL

diameter 35 mm
height 55 mm
0.12 kg
wire springs

CUTOUT

diameter 46-48 mm
min. ceiling thickness 8 mm
recessed depth 85 mm

[a] Colour may deviate slightly due to production conditions

CENO 1.0 Loxone

17616LB3

OPTICAL ACCESSORIES

HONEYCOMB LOUVRE FOR LOXONE

TYPE	COLOUR	VOLTAGE	Ø (MM)	ITEM NUMBER
	Black		29	91523LB0

['17616LB3'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.

© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com