




PROJECT

TYPE


NOTES

QUANTITY

DATE



Round ceiling recessed downlight made from die-cast aluminium; adjustable; surface White Matt; powder coated, matt texture; RAL 9010; inner ring black; with COB (Chip on Board) technology for maximum efficiency; light colour 3000 K; CRI ≥ 90 ; beam angle 31°; 355° rotatable and 60° tiltable; degree of protection IP20; Class 3; IC rated; Loxone ready; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



LUMINAIRE

Ceiling
Semi-Recessed
tilt max 60 °
rotation 355 °
White Matt
RAL 9010 ^a
IP20
IC rated
Interior
530 lm

LED MODULE

3000 K
CRI ≥ 90
L70 / 55000h

OPTICAL

Medium (standard)
beam angle 31°

ELECTRICAL

Loxone
24 V
Class III

PHYSICAL

diameter 35 mm
height 55 mm
0.17 kg
alu plasterkit

CUTOUT

diameter 78-80 mm
recessed depth 80 mm
12,5, 15,25

^a Colour may deviate slightly due to production conditions



16456LW5



OPTICAL ACCESSORIES

Honeycomb Louvre for Loxone

TYPE	COLOUR	VOLTAGE	Ø (MM)	ITEM NUMBER
for CENO Loxone LECA Loxone PIRRO Loxone BLIEK petit Loxone	Black		29	90051133