




PROJECT

TYPE


NOTES

QUANTITY

DATE



Round ceiling recessed downlight made from die-cast aluminium; adjustable; surface Black Matt; powder coated, matt texture; RAL 9011; inner ring black; with COB (Chip on Board) technology for maximum efficiency; light colour 3000 K; CRI \geq 90; beam angle 31°; 355° rotatable and 60° tiltable; degree of protection IP20; Class 3; IC rated; Loxone ready; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

**General**

Ceiling
Semi-Recessed
tilt max 60 °
rotation 355 °
Black Matt
RAL 9011 ^a
IP20
IC rated
Interior
530 lm

LED

3000 K
CRI \geq 90
L70 / 55000h

Optical

Medium (standard)
beam angle 31°

Electrical

excl. driver
24 V
inset 6.0 W ^b
Class III
Standard

Physical

diameter 35 mm
height 55 mm
0.17 kg
alu plasterkit

Cutout

diameter 78-80 mm
recessed depth 80 mm
12,5, 15,25

datasheet.quicksum.material

Aluminium

^a Colour may deviate slightly due to production conditions

^b Without electrical and optical losses



16456LB5



OPTICAL ACCESSORIES

Honeycomb Louver for Loxone

Type

for CENO Loxone | LECA Loxone | PIRRO Loxone |
BLIEK petit Loxone

Colour

Black

Voltage

Ø (MM)

29

Item number

90051133