




## PROJECT

## TYPE


## NOTES

## QUANTITY

## DATE



Round ceiling recessed downlight made from die-cast aluminium; adjustable; surface Black Matt; powder coated, matt texture; RAL 9011; inner ring black; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K; CRI  $\geq$  90; beam angle 31°; 355° rotatable and 60° tiltable; degree of protection IP20; Class 3; IC rated; Loxone ready; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

**General**

Ceiling  
Semi-Recessed  
tilt max 60 °  
rotation 355 °  
Black Matt  
RAL 9011 <sup>a</sup>  
IP20  
IC rated  
Interior  
495 lm

**LED**

2700 K  
CRI  $\geq$  90  
L70 / 55000h

**Optical**

Medium (standard)  
beam angle 31°

**Electrical**

excl. driver  
24 V  
inset 6.0 W <sup>b</sup>  
Class III  
Standard

**Physical**

diameter 35 mm  
height 55 mm  
0.17 kg  
alu plasterkit

**Cutout**

diameter 78-80 mm  
recessed depth 80 mm  
12,5, 15,25

**datasheet.quicksum.material**

Aluminium

<sup>a</sup> Colour may deviate slightly due to production conditions

<sup>b</sup> Without electrical and optical losses



16456LB3



## OPTICAL ACCESSORIES

### Honeycomb Louver for Loxone

#### Type

for CENO Loxone | LECA Loxone | PIRRO Loxone |  
BLIEK petit Loxone

#### Colour

Black

#### Voltage

#### Ø (MM)

29

#### Item number

90051133