



PROJECT

TYPE


NOTES

QUANTITY

DATE



Oval ceiling recessed downlight made from die-cast aluminium; adjustable; surface White Matt; powder coated, matt texture; RAL 9010; inner ring black; installation without tools using wire springs; suitable for ceiling thickness of 4-23 mm; recessed depth 60 mm; with COB (Chip on Board) technology for maximum efficiency; light colour 3000 K; CRI $\geq$ 90; beam angle 31°; 355° rotatable and 60° tiltable; degree of protection IP20; Class 3; IC rated; Loxone ready; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



LUMINAIRE

Ceiling
Semi-Recessed
tilt max 60 °
rotation 355 °
White Matt
RAL 9010 ^a
IP20
IC rated
Interior
2110 lm

LED MODULE

3000 K
CRI $\geq$ 90
L70 / 55000h

OPTICAL

Medium (standard)
beam angle 31°

ELECTRICAL

Loxone
24 V
total insets 24.6 W
Class III

PHYSICAL

diameter 35 mm
height 55 mm
0.4 kg
wire springs

CUTOUT

min. ceiling thickness 4 mm
max. ceiling thickness 23 mm
recessed depth 60 mm
Cut out: 2 x 86-89 | 88

^a Colour may deviate slightly due to production conditions

16426LW5



OPTICAL ACCESSORIES

Honeycomb Louvre for Loxone
TYPE

COLOUR
Black

VOLTAGE

Ø (MM)
29

ITEM NUMBER
91523LB0