



PROJECT

---

TYPE

---

NOTES


---

QUANTITY


---

DATE

---



Oval ceiling recessed downlight made from die-cast aluminium; adjustable; surface White Matt; powder coated, matt texture; RAL 9010; inner ring black; installation without tools using wire springs; suitable for ceiling thickness of 4-23 mm; recessed depth 60 mm; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K; CRI ≥ 90; beam angle 31°; 355° rotatable and 60° tiltable; degree of protection IP20; Class 3; IC rated; Loxone ready; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



**General**

Ceiling  
Semi-Recessed  
tilt max 60 °  
rotation 355 °  
White Matt  
RAL 9010 <sup>a</sup>  
IP20  
IC rated  
Interior  
2020 lm

**LED**

2700 K  
CRI ≥ 90  
L70 / 55000h

**Optical**

Medium (standard)  
beam angle 31°

**Electrical**

excl. driver  
24 V  
inset 12.3 W <sup>b</sup>  
total insets 24.6 W  
Class III  
Standard

**Physical**

diameter 35 mm  
height 55 mm  
0.4 kg  
wire springs

**Cutout**

length 176 mm  
width 87 mm  
min. ceiling thickness 4 mm  
max. ceiling thickness 23 mm  
recessed depth 60 mm

<sup>a</sup> Colour may deviate slightly due to production conditions  
<sup>b</sup> Without electrical and optical losses

16426LW3



## OPTICAL ACCESSORIES

### Honeycomb Louver for Loxone

#### Type

for CENO Loxone | LECA Loxone | PIRRO Loxone |  
BLIEK petit Loxone

#### Colour

Black

#### Voltage

#### Ø (MM)

29

#### Item number

90051133