WEVER & DUCRÉ LIGHTING

SOLID petit 2.0 Loxone

13396LBB3

PROJECT


TYPE

NOTES

QUANTITY

DATE





Cylindrical ceiling surface mounted downlight made from die-cast aluminium; adjustable; surface Black Matt; powder coated, matt texture; RAL 9011; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K; CRI ≥ 90; 24 V; beam angle 31°; 355° rotatable and 25° tiltable; degree of protection IP20; Class 3; Loxone ready; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

LUMINAIRE

Ceiling
Surface
tilt max 25 °
rotation 355 °
Black Matt
RAL 9011 [a]
IP20
Interior
555 lm

LED MODULE

2700 K
CRI ≥ 90
L80 / 100000h
≤ 2 SDCM (initial MacAdam)

OPTICAL

Medium (standard)
beam angle 31°


ELECTRICAL

Loxone
24 V
system 9.0 W
Class III

PHYSICAL

diameter 82 mm
height 130 mm
0.42 kg

[a] Colour may deviate slightly due to production conditions



['13396LBB3'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.

© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com