WEVER & DUCRÉ LIGHTING

PLANO IP44 1.0 Loxone

11886LB3

PROJECT

TYPE


NOTES

QUANTITY

DATE



Squared ceiling recessed downlight made from die-cast aluminium; surface Black Matt; powder coated, matt texture; RAL 9011; installation without tools using wire springs; suitable for ceiling thickness of 4-30 mm; recessed depth 90mm; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K; CRI ≥ 90; beam angle 34°; degree of protection from below IP44; from above IP20; Class 3; Loxone ready; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



LUMINAIRE

Ceiling
Recessed
Black Matt
RAL 9011 [a]
front IP44
back IP20
Interior
550 lm

LED MODULE

2700 K
CRI ≥ 90
L80 / 55000h

OPTICAL

Medium (standard)
beam angle 34°

ELECTRICAL

Loxone
24 V
Class III

PHYSICAL

length 85 mm
width 85 mm
height 89 mm
0.21 kg
wire springs

CUTOUT

length 76 mm
width 78 mm
min. ceiling thickness 4 mm
max. ceiling thickness 30 mm
recessed depth 90 mm

[a] Colour may deviate slightly due to production conditions

['11886LB3'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.

© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com