



**PROJECT**

---

**TYPE**

---

**NOTES**


---

**QUANTITY**


---

**DATE**

---



Round ceiling recessed downlight made from die-cast aluminium; adjustable; surface Black Matt; powder coated, matt texture; RAL 9011; inner ring black; installation without tools using wire springs; suitable for ceiling thickness of 4-25 mm; recessed depth 75 mm; with COB (Chip on Board) technology for maximum efficiency; light colour 3000 K; CRI ≥ 90; beam angle 33°; 355° rotatable and 60° tiltable; degree of protection IP20; Class 3; IC rated; Loxone ready; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



**General**

Ceiling  
Semi-Recessed  
tilt max 60 °  
rotation 355 °  
Black Matt  
RAL 9011 <sup>a</sup>  
IP20  
IC rated  
Interior  
500 lm

**LED**

3000 K  
CRI ≥ 90  
L80 / 55000h

**Optical**

Medium (standard)  
beam angle 33°

**Electrical**

excl. driver  
24 V  
inset 7.0 W <sup>b</sup>  
Class III  
Standard

**Physical**

diameter 135 mm  
height 96 mm  
0.45 kg  
wire springs

**Cutout**

diameter 127 mm  
min. ceiling thickness 4 mm  
max. ceiling thickness 25 mm  
recessed depth 75 mm

**datasheet.quicksum.material**

Aluminium

<sup>a</sup> Colour may deviate slightly due to production conditions  
<sup>b</sup> Without electrical and optical losses

[12536LBB5] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.