



WEVER & DUCRÉ
LIGHTING

BOX 1.0 LED

146164L9 911011G1

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling, Surface

Aluminium Brushed

Inset: Gold

IP20

Interior

Output: 345 lm

CIE flux code: 90 96 99 100 100

LED

colour warm dimming

1800 K - 2850 K

CRI ≥ 95

L70 / 50000 h

4 SDCM

OPTICAL

Medium, Beam angle 32°

ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 7.9 W

Class 1

PHYSICAL

Length 100 mm


Width 100 mm

Height 100 mm


0.74 kg



Squared ceiling surface mounted downlight made from die-cast aluminium; surface Aluminium Brushed; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 1800 K - 2850 K colour warm dimming; binning initial MacAdam ≤ 4 SDCM; CRI ≥ 95 ; 220 - 240 V; degree of protection IP20; PC1; UGR ≤ 19 ; inclusive single inner cover in Gold; light source replaceable by an authorized professional; control gear replaceable by end-user;



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

BOX 1.0 LED

146164L9 911011G1

COMPONENTS

Single Inner Cover

TYPE	L · W · H (MM)	ORDERCODE
BOX max. 10W	62 · 62 · 49	9 1 1 0 1 1 G 1