



WEVER & DUCRÉ
LIGHTING

BOX 1.0 LED

146164L9 911211G1

GENERAL

Ceiling , Surface

Aluminium Brushed

Inset: Gold

IP20

Interior

Output: 380 lm

CIE flux code: 95 99 100 100 100

LED

colour warm dimming

1800 K - 2850 K

CRI ≥ 95

L70 / 50000 h

4 SDCM

OPTICAL

Medium , Beam angle 32°

ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 7.9 W

Class 1

PHYSICAL

Length 100 mm

Width 100 mm

Height 100 mm

0.74 kg


Project

Type


Notes

Quantity

Date



Squared ceiling surface mounted downlight made from die-cast aluminium; surface Aluminium Brushed; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 1800 K - 2850 K colour warm dimming; binning initial MacAdam ≤ 4 SDCM; CRI ≥ 95 ; 220 - 240 V; degree of protection IP20; PC1; UGR ≤ 13 ; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 1500 cd/m²; inclusive single inner reflector in Gold; light source replaceable by an authorized professional; control gear replaceable by end-user;




BOX

1.0 LED

146164L9 911211G1

LIGHT DISTRIBUTION



COMPONENTS

Single Inner Reflector

TYPE	L · W · H (MM)	ORDERCODE
BOX max. 10W	93.5 · 93.5 · 50.5	9 1 1 2 1 1 G 1