



WEVER & DUCRÉ  
LIGHTING

# BOX 1.0 LED

146164L9 911211B1

## GENERAL

Ceiling , Surface

Aluminium Brushed

Inset: Black

IP20

Interior

Output: 375 lm

CIE flux code: 95 100 100 100 100

## LED

colour warm dimming

1800 K - 2850 K

CRI  $\geq 95$

L70 / 50000 h

4 SDCM

## OPTICAL

Medium , Beam angle 32°

## ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 7.9 W

Class 1

## PHYSICAL

Length 100 mm

Width 100 mm

Height 100 mm

0.74 kg


Project

Type


Notes

Quantity

Date



Squared ceiling surface mounted downlight made from die-cast aluminium; surface Aluminium Brushed; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 1800 K - 2850 K colour warm dimming; binning initial MacAdam  $\leq 4$  SDCM; CRI  $\geq 95$ ; 220 - 240 V; degree of protection IP20; PC1; UGR  $\leq 13$ ; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above  $65^\circ \leq 1500$  cd/m<sup>2</sup>; inclusive single inner reflector in Black; light source replaceable by an authorized professional; control gear replaceable by end-user;



BOX

1.0 LED

146164L9 911211B1

LIGHT DISTRIBUTION

