WEVER & DUCRÉ
LIGHTING

DOCUS
2.0 LED

146464W9

Project

Type

Notes

Quantity

Date

GENERAL
Ceiling , Surface
White Matt
RAL 9010 [a]
IP20
Interior
Output: 770 lm
CIE flux code: 95 99 100 100 100

LED
colour warm dimming
1800 K - 2850 K
CRI ≥ 95
L70 / 50000 h
4 SDCM

OPTICAL
Medium , Beam angle 32°

ELECTRICAL
phase-cut dim
220 - 240 V
Total connected power 15.8 W
Class 1

PHYSICAL
Length 174 mm
Width 90 mm
Height 90 mm
0.92 kg

[a] Color may deviate slightly due to production conditions.

Rectangular ceiling surface mounted downlight made from die-cast aluminium; rounded edges; surface White Matt; powder coated; matt texture; RAL 9010; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 1800 K - 2850 K colour warm dimming; binning initial MacAdam ≤ 4 SDCM; CRI ≥ 95; 220 - 240 V; degree of protection IP20; PC1; UGR ≤ 13; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 1500 cd/m²; optional single inner cover available;

['146464W9'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com

WEVER & DUCRÉ
LIGHTING

DOCUS
2.0 LED

146464W9

LIGHT DISTRIBUTION

OPTICAL

Single Inner Cover

TYPE	COLOUR	L·W·H (MM)	ORDERCODE
DOCUS | max. 10W	Black	62·62·39.5	9 1 1 0 2 1 B 1
DOCUS | max. 10W	Gold	62·62·39.5	9 1 1 0 2 1 G 1
DOCUS | max. 10W	White	62·62·39.5	9 1 1 0 2 1 W 1

['146464W9'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com