



WEVER & DUCRÉ
LIGHTING

DOCUS 1.0 LED

146364W9 911021G1

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling , Surface

White Matt

Inset: Gold

RAL 9010^a

IP20

Interior

Output: 345 lm

CIE flux code: 90 96 99 100 100

LED

colour warm dimming

1800 K - 2850 K

CRI \geq 95

L70 / 50000 h

4 SDCM

OPTICAL

Medium , Beam angle 32°

ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 7.9 W

Class 1

PHYSICAL

Length 90 mm

Width 90 mm


Height 92 mm

0.63 kg


^a Color may deviate slightly due to production conditions.



Squared ceiling surface mounted downlight made from die-cast aluminium; rounded edges; surface White Matt; powder coated; matt texture; RAL 9010; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 1800 K - 2850 K colour warm dimming; binning initial MacAdam \leq 4 SDCM; CRI \geq 95; 220 - 240 V; degree of protection IP20; PC1; UGR \leq 19; inclusive single inner cover in Gold;



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

DOCUS 1.0 LED

146364W9 911021G1

COMPONENTS

Single Inner Cover

TYPE	L · W · H (MM)	ORDERCODE
DOCUS max. 10W	62 · 62 · 39,5	9 1 1 0 2 1 G 1