WEVER & DUCRÉ
LIGHTING

ROOMOR
FLOOR 1.2

638120BB2

Project	
Type	
Notes	
Quantity	
Date	

GENERAL

Floor , Standing
Tilt max 45°
Rotation 30°
Black Matt
Mounting Black Matt
RAL 9005 [a]
Shade Black Matt
IP20
Interior
Output: 405[b], 425[c] lm
CIE flux code: 94 98 100 100 88

LED

Lamp PAR16
Socket GU10
max. per socket 15.0 W
CRI ≥ 90

OPTICAL

Shade 2.0

ELECTRICAL

100 - 240 V
LED Inset 6.5 W
Class 1

PHYSICAL

Diameter 250 mm
Height 1590 mm
5.9 kg
cable plug with floor switch

[a] Color may deviate slightly due to production conditions.
[b] PAR16 LAMP 2700K CRI90
[c] PAR16 LAMP 3000K CRI90

Free standing luminaire made from aluminium; surface Black Matt wet painted; matt texture; RAL 9005; cable plug with floor switch; shade Black Matt; wet painted; matt texture; lamp socket GU10; lamp type PAR16; max. 15W; 100 - 240 V; 30° rotatable and 45° tiltable; degree of protection IP20; PC1; lamp not included;

LIGHT DISTRIBUTION

— C0/C180

['638120BB2'] The technical data represent rated values for an ambient temperature of 25ºC. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever &amp; Ducré BV apply.

© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com

May 8, 2024

1/2

WEVER & DUCRÉ
LIGHTING

ROOMOR
FLOOR 1.2

638120BB2

LAMPS

PAR16 LED Lamp

TYPE	COLOUR	Ø·H (MM)	ORDERCODE
2700K | >90 CRI | GU10	Black	⌀50·60	9 0 1 2 2 8 B 3
3000K | >90 CRI | GU10	Black	⌀50·60	9 0 1 2 2 8 B 5
2700K | >90 CRI | GU10	White	⌀50·60	9 0 1 2 2 8 W 3
3000K | >90 CRI | GU10	White	⌀50·60	9 0 1 2 2 8 W 5
2700K | >80 CRI | GU10	Silver	⌀50·60	9 0 5 2 2 7 S 2
3000K | >80 CRI | GU10	Silver	⌀50·60	9 0 5 2 2 7 S 4