WEVER & DUCRÉ LIGHTING

ROOMOR CABLE 1.1 PAR16

248120BB1

PROJECT

TYPE


NOTES

QUANTITY

DATE



Suspended luminaire made from aluminium; surface Black Matt wet painted; matt texture; RAL 9011; shade Black Matt; wet painted; matt texture; cable and ceiling base in black; lamp socket GU10; lamp type PAR16; max. 15W; 100 - 240 V; degree of protection IP20; Class 1; lamp not included;



LUMINAIRE

Ceiling
Suspended
Mounting: Black Matt
RAL 9011 [a]
Shade Black Matt
IP20
Interior

LAMP

lamp PAR16
socket GU10
max. per socket 12.0 W
CRI ≥ 90

OPTICAL

Shade 1.0

ELECTRICAL

100 - 240 V
Class I

PHYSICAL

diameter 205 mm
height 215 mm
0.8 kg
cable length 2500 mm


[a] Colour may deviate slightly due to production conditions


MEASURED LAMPS

PAR16 LAMP 2700K CRI90
445 lm

PAR16 LAMP 3000K CRI90
465 lm

LIGHT DISTRIBUTION





ROOMOR CABLE 1.1 PAR16

248120BB1

ELECTRICAL ACCESSORIES

LED LAMPS

TYPE	COLOUR	VOLTAGE	ITEM NUMBER
	Black Texture		W901228B3
	Black Texture		W901228B5

LAMPS

PAR16 LED LAMP

TYPE	COLOUR	VOLTAGE	Ø·H (MM)	ITEM NUMBER
2700K | >90 CRI | GU10 | 220-240VAC	White		50·60	901228W3
3000K | >90 CRI | GU10 | 220-240VAC	White		50·60	901228W5
2700K | >80 CRI | GU10 | 220-240VAC	Silver		50·55	905227S2
3000K | >80 CRI | GU10 | 220-240VAC	Silver		50·55	905227S4

['248120BB1'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.

© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com