



WEVER & DUCRÉ
LIGHTING

BOX 2.0 PAR16

146220L0 911251G1

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling, Surface

Aluminium Brushed

Inset: Gold

IP20

Interior

Output: 770 lm

CIE flux code: 90 98 100 100 100

LED

Lamp 2 x PAR16

Socket GU10

max. per socket 12.0 W

CRI ≥ 80

ELECTRICAL

100 - 240 V

LED Inset 8.8 W

Class 1

PHYSICAL

Length 188 mm


Width 100 mm

Height 100 mm


1.13 kg



Rectangular ceiling surface mounted downlight made from die-cast aluminium; surface Aluminium Brushed; lamp socket GU10; lamp type PAR16; 2x max. 12W; 100 - 240 V; degree of protection IP20; PC1; $UGR \leq 16$; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above $65^\circ \leq 1500 \text{ cd/m}^2$; lamp not included; inclusive double inner reflector in Gold;



LIGHT DISTRIBUTION



BOX

2.0 PAR16

146220L0 911251G1

LAMPS

PAR16 LED Lamp

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
2700K >90 CRI GU10	Black	ø50-60	9 0 1 2 2 8 B 3
3000K >90 CRI GU10	Black	ø50-60	9 0 1 2 2 8 B 5
2700K >90 CRI GU10	White	ø50-60	9 0 1 2 2 8 W 3
3000K >90 CRI GU10	White	ø50-60	9 0 1 2 2 8 W 5
2700K >80 CRI GU10	Silver	ø50-60	9 0 5 2 2 7 S 2
3000K >80 CRI GU10	Silver	ø50-60	9 0 5 2 2 7 S 4

INNER COVER

Single Inner Cover

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
BOX max. 10W	Black	62-62-49	9 1 1 0 1 1 B 1
BOX max. 10W	Gold	62-62-49	9 1 1 0 1 1 G 1
BOX max. 10W	Champagne	62-62-49	9 1 1 0 1 1 M 1
BOX max. 10W	White	62-62-49	9 1 1 0 1 1 W 1

INNER REFLECTOR

Double Inner Reflector

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
BOX 2.0 max. 10W	Black	181-93-50	9 1 1 2 5 1 B 1
BOX 2.0 max. 10W	Gold	181-93-50	9 1 1 2 5 1 G 1
BOX 2.0 max. 10W	Champagne	181-93-50	9 1 1 2 5 1 M 1
BOX 2.0 max. 10W	White	181-93-50	9 1 1 2 5 1 W 1