



**PROJECT** \_\_\_\_\_

**TYPE** \_\_\_\_\_


**NOTES** \_\_\_\_\_

**QUANTITY** \_\_\_\_\_

**DATE** \_\_\_\_\_



Tubular wall surface luminaire made from aluminium; surface Black Matt; powder coated; matt texture; RAL 9011; cable plug with switch in black; phase-cut dim; light colour 3000 K; CRI ≥ 90; 220 - 240 V; degree of protection IP20; Class 2; light source replaceable by end-user;



**LUMINAIRE**

Wall \_\_\_\_\_

Surface \_\_\_\_\_

Black Matt \_\_\_\_\_

RAL 9011<sup>a</sup> \_\_\_\_\_

IP20 \_\_\_\_\_

Interior \_\_\_\_\_

2940 lm \_\_\_\_\_

**LED Module**

3000 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

L70 / 50000h \_\_\_\_\_

≤ 3 SDCM (initial MacAdam) \_\_\_\_\_

**Optical**

Opal \_\_\_\_\_

CIE flux code: 40 70 89 90 100 \_\_\_\_\_

**Electrical**

phase-cut dim \_\_\_\_\_

220 - 240 V \_\_\_\_\_

system 23.0 W \_\_\_\_\_

Class II \_\_\_\_\_

Standard \_\_\_\_\_

**Physical**

length 33 mm \_\_\_\_\_

width 1626 mm \_\_\_\_\_

height 33 mm \_\_\_\_\_

0.33 kg \_\_\_\_\_

cable plug with switch \_\_\_\_\_

**datasheet.quicksum.material**

Polycarbonate \_\_\_\_\_

<sup>a</sup> Colour may deviate slightly due to production conditions

**LIGHT DISTRIBUTION**

