WEVER & DUCRÉ LIGHTING DARF **WALL 1.1**

2563T7B4

GENERAL

Wall , Surface
Black Matt
RAL 9005 ^a
IP20
Interior
Output: 3560 lm
CIE flux code: 36 64 84 71 100

LED

3000 K
$CRI \ge 80$
L70/60000h
3 SDCM

OPTICAL

Opal	

ELECTRICAL

non dim	
220 - 240 V	
Total connected power 22.1 W	
Class 2	

PHYSICAL

Length 33 mm
Width 1626 mm
Height 33 mm
0.33 kg
cable plug with switch

^a Color may deviate slightly due to production conditions

Project

Type


Notes

Date


Quantity



Tubular wall surface luminaire made from aluminium; surface Black Matt; powder coated; matt texture; RAL 9005; non dim; light colour 3000 K; CRI \geq 80; 220 - 240 V; degree of protection IP20; PC2; light source replaceable by end-user;



LIGHT DISTRIBUTION



['2563T7B4'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & amp; amp; Ducré BV apply. March 28, 2024



['2563T7B4'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & amp; amp; Ducré BV apply. March 28, 2024