



WEVER & DUCRÉ
LIGHTING

BLIEK ROUND 1.0 PAR16

125120W0

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling , Semi-Recessed

Tilt max 60°

Rotation 350°

White Matt

RAL 9010 ^a

IP20

IC rated

Interior

Output: 505^b, 550^c lm

CIE flux code: 94 98 100 100 100

LED

Lamp PAR16

Socket GU10

max. per socket 12.0 W

CRI ≥ 90

ELECTRICAL

100 - 240 V

LED Inset 6.5 W

Class 2

PHYSICAL

Diameter 135 mm

Height 61 mm

0.42 kg

wire springs

CUTOUT

Diameter 127 mm

Min. ceiling thickness 4 mm


Max. ceiling thickness 25 mm

Recessed depth 75 mm


^a Color may deviate slightly due to production conditions.

^b PAR16 LAMP 2700K CRI90


^c PAR16 LAMP 3000K CRI90



Round ceiling recessed downlight made from die-cast aluminium; adjustable; surface White Matt; powder coated, matt texture; RAL 9010; inner ring black; installation without tools using wire springs; suitable for ceiling thickness of 4-25 mm; recessed depth 75 mm; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; 350° rotatable and 60° tiltable; degree of protection IP20; PC2; IC rated; lamp not included;



LIGHT DISTRIBUTION



BLIEK

ROUND 1.0 PAR16

125120W0

LAMPS

PAR16 LED Lamp

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
2700K >90 CRI GU10	Black	ø50 · 60	9 0 1 2 2 8 B 3
3000K >90 CRI GU10	Black	ø50 · 60	9 0 1 2 2 8 B 5
2700K >90 CRI GU10	White	ø50 · 60	9 0 1 2 2 8 W 3
3000K >90 CRI GU10	White	ø50 · 60	9 0 1 2 2 8 W 5
2700K >80 CRI GU10	Silver	ø50 · 60	9 0 5 2 2 7 S 2
3000K >80 CRI GU10	Silver	ø50 · 60	9 0 5 2 2 7 S 4