

ROOMORCABLE 1.1 PAR16

248220GG1

Project
Туре
Notes
Quantity
Date

GENERAL				
Ceiling, Suspended				
Cement Grey				
Mounting Cement Grey				
RAL 7033 ^a				
Shade Cement Grey + White Matt				
IP20				
Interior				
Output: 450 ^b , 470 ^c lm				
CIE flux code: 94 98 100 100 98				
LED				
Lamp PAR16				
Socket GU10				

CRI ≥ 90 OPTICAL

max. per socket 15.0 W

Shade 1.0

ELECTRICAL

100 - 240 V LED Inset 6.5 W Class 1

PHYSICAL

Diameter 205 mm Height 215 mm 0.8 kg


- ^a Color may deviate slightly due to production conditions.
- ^b PAR16 LAMP 2700K CRI90
- $^{\rm c}$ PAR16 LAMP 3000K CRI90








Suspended luminaire made from aluminium; surface Cement Grey wet painted; matt texture; RAL 7033; cable and ceiling base in Cement Grey; shade Cement Grey + White Matt; wet painted; matt texture; lamp socket GU10; lamp type PAR16; max. 15W; 100 - 240 V; degree of protection IP20; PC1; lamp not included;



LIGHT DISTRIBUTION





ROOMORCABLE 1.1 PAR16

248220GG1

LAMPS

PAR16 LED Lamp

TYPE	COLOUR	Ø∙H (MM)	ORDERCODE
2700K >90 CRI GU10	Black	Ø50·60	901228B3
3000K >90 CRI GU10	Black	ø50·60	901228B5
2700K >90 CRI GU10	White	ø50·60	901228W3
3000K >90 CRI GU10	White	ø50·60	901228W5
2700K >80 CRI GU10	Silver	ø50·60	905227S2
3000K >80 CRI GU10	Silver	ø50·60	90522784

April 25, 2024