WEVER & DUCRÉ

# **ROOMOR** CABLE 1.2 PAR16

248220BF2

#### GENERAL

Ceiling, Suspended
Black Matt
Mounting Black Matt
RAL 9005 <sup>a</sup>
Shade Felt Grey
IP20
Interior
Output: 415 <sup>b</sup> , 430 <sup>c</sup> lm
CIE flux code: 94 98 100 100 90

#### LED

Lamp PAR16
Socket GU10
max. per socket 15.0 W
$CRI \ge 90$

# OPTICAL

Shade 2.0

# ELECTRICAL

100 - 240 V
LED Inset 6.5 W
Class 1

#### PHYSICAL

Diameter 250 mm
Height 295 mm
0.89 kg

<sup>a</sup> Color may deviate slightly due to production conditions.

<sup>b</sup> PAR16 LAMP 2700K CRI90


<sup>c</sup> PAR16 LAMP 3000K CRI90

Project
Туре
Notes
Quantity
Date






Suspended luminaire made from aluminium; surface Black Matt wet painted; matt texture; RAL 9005; cable and ceiling base in Black Matt; shade Felt Grey; lamp socket GU10; lamp type PAR16; max. 15W; 100 - 240 V; degree of protection IP20; PC1; lamp not included;



# LIGHT DISTRIBUTION



['248220BF2'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & amp; amp; Ducré BV apply. © Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com

May 9, 2024

WEVER & DUCRÉ ROOMOR CABLE 1.2 PAR16

248220BF2

### LAMPS

#### PAR16 LED Lamp

ТҮРЕ	COLOUR	Ø∙H (MM)	ORDERCODE
2700K   >90 CRI   GU10	Black	ø50·60	901228B3
3000K   >90 CRI   GU10	Black	ø50·60	901228B5
2700K   >90 CRI   GU10	White	ø50.60	901228W3
3000K   >90 CRI   GU10	White	ø50·60	901228W5
2700K   >80 CRI   GU10	Silver	ø50·60	9 0 5 2 2 7 S 2
3000K   >80 CRI   GU10	Silver	ø50·60	90522754

['248220BF2'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & amp; amp; Ducré BV apply. May 9, 2024