



PROJECT _____

TYPE _____


NOTES _____

QUANTITY _____

DATE _____



Cylindrical ceiling surface mounted downlight made from die-cast aluminium; surface White Matt; powder coated; matt texture; RAL 9010; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; degree of protection IP20; Class 1; optional inner reflector available; lamp not included;



LUMINAIRE

Ceiling _____
 Surface _____
 White Matt _____
 RAL 9010 ^a _____
 IP20 _____
 Interior _____

LAMP

lamp PAR16 _____
 socket GU10 _____
 max. per socket 12.0 W _____
 CRI ≥ 80 / 90 / 90 _____

Electrical

100 - 240 V _____
 Class I _____
 Standard _____

Physical

diameter 70 mm _____
 height 82 mm _____
 0.14 kg _____

datasheet.quicksum.material

Aluminium _____

^a Colour may deviate slightly due to production conditions




MEASURED LAMPS

PAR16 LAMP 3000K CRI90 _____
 515 lm _____
 6 W _____

PAR16 LAMP 2700K CRI90 _____
 500 lm _____
 6.1 W _____

PAR16 LAMP 2700K CRI80 _____
 365 lm _____
 4.4 W _____

LIGHT DISTRIBUTION



[‘258220W0’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.



OPTICAL ACCESSORIES

Inner Reflector

Type	Colour	Voltage	Item number
RAY mini max. 10W	Black		900199B4
RAY mini max. 10W	Gold		900199G4
RAY mini max. 10W	Champagne		900199M4
RAY mini max. 10W	Bronze		900199Q4
RAY mini max. 10W	White		900199W4

ELECTRICAL ACCESSORIES

LED LAMPS

Type	Colour	Voltage	Item number
	Black Texture		W901228B3
	Black Texture		W901228B5

LAMPS

PAR16 LED Lamp

Type	Colour	Voltage	Ø·H (MM)	Item number
2700K >90 CRI GU10	White		50-60	901228W3
3000K >90 CRI GU10	White		50-60	901228W5
2700K >80 CRI GU10	Silver		50-55	905227S2
3000K >80 CRI GU10	Silver		50-55	905227S4