

PIRRO OPAL 4.0

151484J5

GENERAL

Ceiling , Surface
White Matt + Gold
RAL 9010 ^a
IP20
Interior
Output: 710 lm
CIE flux code: 65 94 100 100 100

LED

3000 K
CRI ≥ 90
L80 / 60000h
3 SDCM

OPTICAL

Opal

ELECTRICAL

phase-cut dim
220 - 240 V
Total connected power 12.0 W
Class I

PHYSICAL

Length 182 mm
Width 50 mm
Height 65 mm
0.52 kg

^a Color may deviate slightly due to production conditions.

Project _____

Type _____


Notes _____

Quantity _____


Date _____



Rectangular ceiling surface mounted downlight made from die-cast aluminium with opal PMMA cover; surface housing White Matt powder coated; matt texture; with aesthetic frame in Gold wet painted; matt smooth; PCB 3-step binning; phase-cut dim; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; CRI (Colour Rendering Index) ≥ 90 ; degree of protection IP20; PC1; driver included; light source replaceable by an authorized professional; control gear replaceable by end-user;



LIGHT DISTRIBUTION



PIRRO
OPAL 4.0

151484J5

MOUNTING

1.0 CEILING BASE

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
PIRRO SYSTEM	White	754 · 51 · 12	9 0 0 5 2 0 7 2
PIRRO SYSTEM	Black	754 · 51 · 12	9 0 0 5 2 0 7 3
PIRRO SYSTEM	Gold	754 · 51 · 12	9 0 0 5 2 0 7 4

2.0 CEILING BASE

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
PIRRO SYSTEM	White	1150 · 51 · 12	9 0 0 5 2 0 7 5
PIRRO SYSTEM	Black	1150 · 51 · 12	9 0 0 5 2 0 7 6
PIRRO SYSTEM	Gold	1150 · 51 · 12	9 0 0 5 2 0 7 7