

# PIRRO OPAL 4.0

151484E5

Project

Type

Notes

Quantity

Date

## GENERAL

Ceiling, Surface

White Matt + Black Matt

RAL 9003 + RAL 9005<sup>a</sup>

IP20

Interior

Output: 620 lm

CIE flux code: 65 94 100 100 100

## LED

3000 K

CRI  $\geq 90$

L80 / 60000h

3 SDCM

## OPTICAL

Opal

## ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 12.0 W

Class 1

## PHYSICAL

Length 182 mm

Width 50 mm


Height 65 mm

0.52 kg


<sup>a</sup> Color may deviate slightly due to production conditions.



Rectangular ceiling surface mounted downlight made from die-cast aluminium with opal PMMA cover; surface housing White Matt powder coated; matt texture; with aesthetic frame in Black Matt wet painted; matt fine texture; PCB 3-step binning; phase-cut dim; light colour 3000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 90$ ; CRI (Colour Rendering Index)  $\geq 90$ ; degree of protection IP20; PCI; driver included; light source replaceable by an authorized professional; control gear replaceable by end-user;



## LIGHT DISTRIBUTION



PIRRO

OPAL 4.0

151484E5

MOUNTING

1.0 CEILING BASE

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
PIRRO SYSTEM	White	754 · 51 · 12	9 0 0 5 2 0 7 2
PIRRO SYSTEM	Black	754 · 51 · 12	9 0 0 5 2 0 7 3
PIRRO SYSTEM	Gold	754 · 51 · 12	9 0 0 5 2 0 7 4

2.0 CEILING BASE

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
PIRRO SYSTEM	White	1150 · 51 · 12	9 0 0 5 2 0 7 5
PIRRO SYSTEM	Black	1150 · 51 · 12	9 0 0 5 2 0 7 6
PIRRO SYSTEM	Gold	1150 · 51 · 12	9 0 0 5 2 0 7 7