

# PIRRO OPAL 2.0

151284B5

## GENERAL

Ceiling , Surface  
Black Matt  
RAL 9005 <sup>a</sup>  
IP20  
Interior  
Output: 240 lm  
CIE flux code: 65 94 100 100 100

## LED

3000 K  
CRI  $\geq 90$   
L80 / 60000h  
3 SDCM

## OPTICAL

Opal

## ELECTRICAL

phase-cut dim  
220 - 240 V  
Total connected power 6.6 W  
Class 1

## PHYSICAL

Length 94 mm  
Width 50 mm  
Height 65 mm  
0.3 kg

<sup>a</sup> Color may deviate slightly due to production conditions.

Project \_\_\_\_\_

Type \_\_\_\_\_


Notes \_\_\_\_\_

Quantity \_\_\_\_\_


Date \_\_\_\_\_



Rectangular ceiling surface mounted downlight made from die-cast aluminium with opal PMMA cover; surface housing Black Matt powder coated; matt texture; with aesthetic frame in Black Matt wet painted; matt fine texture; PCB 3-step binning; phase-cut dim; light colour 3000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 90$ ; CRI (Colour Rendering Index)  $\geq 90$ ; degree of protection IP20; PCI; driver included; light source replaceable by an authorized professional; control gear replaceable by end-user;



## LIGHT DISTRIBUTION



PIRRO  
OPAL 2.0

151284B5

MOUNTING

1.0 CEILING BASE

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
PIRRO SYSTEM	White	754 · 51 · 12	9 0 0 5 2 0 7 2
PIRRO SYSTEM	Black	754 · 51 · 12	9 0 0 5 2 0 7 3
PIRRO SYSTEM	Gold	754 · 51 · 12	9 0 0 5 2 0 7 4

2.0 CEILING BASE

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
PIRRO SYSTEM	White	1150 · 51 · 12	9 0 0 5 2 0 7 5
PIRRO SYSTEM	Black	1150 · 51 · 12	9 0 0 5 2 0 7 6
PIRRO SYSTEM	Gold	1150 · 51 · 12	9 0 0 5 2 0 7 7