

PIRRO OPAL 2.0

151284B3

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling, Surface

Black Matt

RAL 9005 ^a

IP20

Interior

Output: 220 lm

CIE flux code: 65 94 100 100 100

LED

2700 K

CRI ≥ 90

L80 / 60000h

3 SDCM

OPTICAL

Opal

ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 6.6 W

Class I

PHYSICAL

Length 94 mm

Width 50 mm


Height 65 mm

0.3 kg


^a Color may deviate slightly due to production conditions.



Rectangular ceiling surface mounted downlight made from die-cast aluminium with opal PMMA cover; surface housing Black Matt powder coated; matt texture; with aesthetic frame in Black Matt wet painted; matt fine texture; PCB 3-step binning; phase-cut dim; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; CRI (Colour Rendering Index) ≥ 90 ; degree of protection IP20; PCI; driver included; light source replaceable by an authorized professional; control gear replaceable by end-user;



LIGHT DISTRIBUTION



PIRRO
OPAL 2.0

151284B3

MOUNTING

1.0 CEILING BASE

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
PIRRO SYSTEM	White	754 · 51 · 12	9 0 0 5 2 0 7 2
PIRRO SYSTEM	Black	754 · 51 · 12	9 0 0 5 2 0 7 3
PIRRO SYSTEM	Gold	754 · 51 · 12	9 0 0 5 2 0 7 4

2.0 CEILING BASE

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
PIRRO SYSTEM	White	1150 · 51 · 12	9 0 0 5 2 0 7 5
PIRRO SYSTEM	Black	1150 · 51 · 12	9 0 0 5 2 0 7 6
PIRRO SYSTEM	Gold	1150 · 51 · 12	9 0 0 5 2 0 7 7