



WEVER & DUCRÉ
LIGHTING

PIRRO SPOT SURFACE 2.0

151264B5

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling , Surface

Black Matt

RAL 9005 ^a

IP20

Interior

Output: 715 lm

CIE flux code: 99 100 100 100 100

LED

3000 K

CRI ≥ 90

L70 / 55000h

2 SDCM

OPTICAL

Medium , Beam angle 32°

ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 11.0 W

Class 1

PHYSICAL

Length 94 mm

Width 50 mm


Height 80 mm

0.3 kg

^a Color may deviate slightly due to production conditions.



Rectangular ceiling surface mounted downlight made from die-cast aluminium; housing Black Matt powder coated; matt texture; with reflector in Black Matt wet painted; matt fine texture; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; degree of protection IP20; PC1; UGR ≤ 13 ; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 1500 cd/m²; driver included; optional honeycomb louver available, to reduce glare; light source replaceable by an authorized professional; control gear replaceable by end-user;






WEVER & DUCRÉ
LIGHTING

PIRRO

SPOT SURFACE 2.0

151264B5

LIGHT DISTRIBUTION



Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.9	0.88	0.85	0.83	0.81
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

MOUNTING

1.0 CEILING BASE

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
PIRRO SYSTEM	White	754 · 51 · 12	9 0 0 5 2 0 7 2
PIRRO SYSTEM	Black	754 · 51 · 12	9 0 0 5 2 0 7 3
PIRRO SYSTEM	Gold	754 · 51 · 12	9 0 0 5 2 0 7 4

2.0 CEILING BASE

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
PIRRO SYSTEM	White	1150 · 51 · 12	9 0 0 5 2 0 7 5
PIRRO SYSTEM	Black	1150 · 51 · 12	9 0 0 5 2 0 7 6
PIRRO SYSTEM	Gold	1150 · 51 · 12	9 0 0 5 2 0 7 7

OPTICAL

Honeycomb Louver

TYPE	Ø (MM)	ORDERCODE
BLIEK PETIT CENO LECA PIRRO	29	9 0 0 5 1 1 3 1