

STIPO 4.0

737468Q5

GENERAL

Floor , Standing
Tilt max 135°
Bronze
IP65
Exterior
Output: 500 lm
CIE flux code: 93 99 100 100 100

LED

3000 K
CRI ≥ 90
L70 / 55000h
3 SDCM

OPTICAL

Flood , Beam angle 38°
UGR < 19

ELECTRICAL

phase-cut dim
220 - 240 V
Total connected power 6.7 W
Class 2

PHYSICAL

Diameter 52 mm
Height 120 mm
0.52 kg


Project _____

Type _____

Notes _____

Quantity _____


Date _____



Cylindrical outdoor floor projector; surface Bronze; powder coated; matt texture; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; CRI ≥ 90; 220 - 240 V; 135° tiltable; degree of protection IP65; PC2; fixation base not included; driver included; optional ground spike available; light source replaceable by an authorized professional;



LIGHT DISTRIBUTION



STIPO
4.0

737468Q5

GROUND SPIKE

Ground Spike

TYPE	Ø · H (MM)	ORDERCODE
STAKE 1.0	Ø43 · 212	9 0 0 1 3 1 0 6

POLE

POLE 200

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
STIPO with fixation plate	Anthracite Grey	Ø45 · 200	9 1 0 0 6 2 A 0
STIPO with fixation plate	Bronze	Ø45 · 200	9 1 0 0 6 2 Q 0

POLE 400

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
STIPO with fixation plate	Anthracite Grey	Ø45 · 400	9 1 0 0 6 4 A 0
STIPO with fixation plate	Bronze	Ø45 · 400	9 1 0 0 6 4 Q 0

POLE 600

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
STIPO with fixation plate	Anthracite Grey	Ø45 · 600	9 1 0 0 6 6 A 0
STIPO with fixation plate	Bronze	Ø45 · 600	9 1 0 0 6 6 Q 0