

STIPO 4.0

737468A5

GENERAL

Floor , Standing

Tilt max 135°

Anthracite Grey

RAL 7016 ^a

IP65

Exterior

Output: 500 lm

CIE flux code: 93 99 100 100 100

LED

3000 K

CRI ≥ 90

L70 / 55000h

3 SDCM

OPTICAL

Flood , Beam angle 38°

UGR < 19

ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 6.7 W

Class 2

PHYSICAL

Diameter 52 mm

Height 120 mm

0.52 kg

^a Color may deviate slightly due to production conditions.

Project



Type

Notes

Quantity

Date




IP65    

Cylindrical outdoor floor projector; surface Anthracite Grey; powder coated; matt texture; RAL 7016; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; CRI ≥ 90; 220 - 240 V; 135° tiltable; degree of protection IP65; PC2; fixation base not included; driver included; optional ground spike available; light source replaceable by an authorized professional;



LIGHT DISTRIBUTION



STIPO
4.0

737468A5

GROUND SPIKE

Ground Spike

TYPE	Ø · H (MM)	ORDERCODE
STAKE 1.0	Ø 43 · 212	9 0 0 1 3 1 0 6

POLE

POLE 200

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
STIPO with fixation plate	Anthracite Grey	Ø 45 · 200	9 1 0 0 6 2 A 0
STIPO with fixation plate	Bronze	Ø 45 · 200	9 1 0 0 6 2 Q 0

POLE 400

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
STIPO with fixation plate	Anthracite Grey	Ø 45 · 400	9 1 0 0 6 4 A 0
STIPO with fixation plate	Bronze	Ø 45 · 400	9 1 0 0 6 4 Q 0

POLE 600

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
STIPO with fixation plate	Anthracite Grey	Ø 45 · 600	9 1 0 0 6 6 A 0
STIPO with fixation plate	Bronze	Ø 45 · 600	9 1 0 0 6 6 Q 0