



PROJECT

TYPE


NOTES

QUANTITY

DATE



Cylindrical outdoor floor projector; surface Anthracite Grey; powder coated; matt texture; RAL 7016; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; CRI ≥ 90 ; 220 - 240 V; 135° tiltable; degree of protection IP65; Class 2; driver included; optional ground spike available; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



LUMINAIRE

Floor
Standing
tilt max 135 °
Anthracite Grey
RAL 7016 ^a
IP65
Exterior
500 lm


LED Module

3000 K
CRI ≥ 90
L70 / 55000h
 ≤ 3 SDCM (initial MacAdam)

Optical

Medium (standard)
beam angle 38°
UGR ≤ 19
CIE flux code: 93 99 100 100 100

LIGHT DISTRIBUTION



Electrical

phase-cut dim
220 - 240 V
system 6.7 W
Class II
Standard

Physical

diameter 52 mm
height 120 mm
0.56 kg

datasheet.quicksum.material

Aluminum

^a Colour may deviate slightly due to production conditions

737268A5



BASE

**Ground Spike
Type**

STAKE 1.0

Colour

Voltage

Ø·H (MM)

43·212

Item number

90013106