



PROJECT _____

TYPE _____


NOTES _____

QUANTITY _____

DATE _____



Cylindrical outdoor floor projector; surface Bronze; powder coated; matt texture; RAL 075 30 10; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; CRI \geq 90; 220 - 240 V; 135° tiltable; degree of protection IP65; Class 2; driver included; optional ground spike available; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



LUMINAIRE

Floor _____
 Standing _____
 tilt max 135° _____
 Bronze _____
 RAL 075 30 10^a _____
 IP65 _____
 Exterior _____
 450 lm _____

LED Module

3000 K _____
 CRI \geq 90 _____
 L70 / 55000h _____
 \leq 3 SDCM (initial MacAdam) _____

Optical

Medium (standard) _____
 beam angle 38° _____
 UGR \leq 13 _____
 CIE flux code: 97 100 100 100 _____
 100 _____
 \geq 65° < 3000 cd/m² _____

Electrical

phase-cut dim _____
 220 - 240 V _____
 system 6.7 W _____
 Class II _____
 Standard _____

Physical


diameter 52 mm _____
 height 164 mm _____
 0.59 kg _____

datasheet.quicksum.material

Aluminium _____

^a Colour may deviate slightly due to production conditions

LIGHT DISTRIBUTION



737168Q5



BASE

**Ground Spike
Type**

STAKE 1.0

Colour

Voltage

Ø·H (MM)

43·212

Item number

90013106