

# STIPO 1.0

737168A5

Project

Type

Notes

Quantity

Date

## GENERAL

Floor , Standing

Tilt max 135°

Anthracite Grey

RAL 7016 <sup>a</sup>

IP65

Exterior

Output: 450 lm

CIE flux code: 97 100 100 100 100

## LED

3000 K

CRI ≥ 90

L70 / 55000h

3 SDCM

## OPTICAL

Flood , Beam angle 38°

UGR < 19

## ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 6.7 W

Class 2

## PHYSICAL





Diameter 52 mm

Height 164 mm


0.59 kg

<sup>a</sup> Color may deviate slightly due to production conditions.




IP65    

Cylindrical outdoor floor projector; surface Anthracite Grey; powder coated; matt texture; RAL 7016; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; CRI ≥ 90; 220 - 240 V; 135° tiltable; degree of protection IP65; PC2; driver included; optional ground spike available; light source replaceable by an authorized professional;



## LIGHT DISTRIBUTION





# STIPO 1.0

737168A5

## MOUNTING

### Ground Spike

TYPE	Ø · H (MM)	ORDERCODE
STAKE 1.0	Ø43 · 212	9 0 0 1 3 1 0 6