

**GENERAL**

Wall , Surface

Bronze

IP65

Exterior

Output: 295 lm

CIE flux code: 48 83 98 100 100

**LED**

2700 K

CRI  $\geq 90$

L80 / 60000 h

3 SDCM

**ELECTRICAL**

phase-cut dim

220 - 240 V

Total connected power 8.0 W


Class 1

**PHYSICAL**


Diameter 185 mm

Height 110 mm


0.91 kg



Wall surface luminaire made from die-cast aluminium; surface Bronze; powder coated; matt texture; up or down light emission; PCB 3-step binning; phase-cut dim; light colour 2700 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 90$ ; 220 - 240 V; degree of protection IP65; PC1; light source replaceable by an authorized professional;



**LIGHT DISTRIBUTION**



SWAM  
1.0

746278Q3

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.95	0.92	0.89	0.86
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF		RSMF <sup>a</sup>	Room Surface Maintenance Factor	
MF	Maintenance Factor		LLMF	Lamp Lumens Maintenance Factor	
LMF <sup>a</sup>	Luminaire Maintenance Factor		LSF	Lamp Survival Faktor	

<sup>a</sup> According to “CIE 97, Maintenance of indoor electric lighting systems”, 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.