



WEVER & DUCRÉ
LIGHTING

SWAM FLOOR 1.0

746178Q3

Project

Type

Notes

Quantity

Date

GENERAL

Floor , Standing

Bronze

IP65

Exterior

Output: 245 lm

CIE flux code: 49 85 99 100 100

LED

2700 K

CRI ≥ 90

L80 / 60000h

3 SDCM

ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 8.2 W

Class 1

PHYSICAL


Diameter 185 mm

Height 110 mm


0.97 kg



Floor surface mounted luminaire made from die-cast aluminium; surface Bronze; powder coated; matt texture; PCB 3-step binning; phase-cut dim; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; 220 - 240 V; to be combined with straight base or curved base; optional ground spike available; degree of protection IP65; PC1; light source replaceable by an authorized professional;



LIGHT DISTRIBUTION



SWAM
FLOOR 1.0

746178Q3

FIXATION

Ground Fixation Plate

TYPE	Ø · H (MM)	ORDERCODE
KIOSK SWAM	Ø80 · 10	9 0 0 1 9 0 1 9

POLE

POLE 400 STRAIGHT

TYPE	COLOUR	LENGTH (MM)	ORDERCODE
SWAM	Black	400	9 1 0 0 9 0 B 0
SWAM	Bronze	400	9 1 0 0 9 0 Q 0

POLE 600 STRAIGHT

TYPE	COLOUR	LENGTH (MM)	ORDERCODE
SWAM	Black	600	9 1 0 0 9 1 B 0
SWAM	Bronze	600	9 1 0 0 9 1 Q 0

POLE 800 STRAIGHT

TYPE	COLOUR	LENGTH (MM)	ORDERCODE
SWAM	Black	800	9 1 0 0 9 2 B 0
SWAM	Bronze	800	9 1 0 0 9 2 Q 0

POLE 400 CURVED

TYPE	COLOUR	LENGTH (MM)	ORDERCODE
SWAM	Black	400	9 1 0 0 9 3 B 0
SWAM	Bronze	400	9 1 0 0 9 3 Q 0

POLE 600 CURVED

TYPE	COLOUR	LENGTH (MM)	ORDERCODE
SWAM	Black	600	9 1 0 0 9 4 B 0
SWAM	Bronze	600	9 1 0 0 9 4 Q 0

POLE 800 CURVED

TYPE	COLOUR	LENGTH (MM)	ORDERCODE
SWAM	Black	800	9 1 0 0 9 5 B 0
SWAM	Bronze	800	9 1 0 0 9 5 Q 0