



WEVER & DUCRÉ
LIGHTING

BLIEK ROUND 1.0 LED

125361K3C

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling , Semi-Recessed

Tilt max 60°

Rotation 355°

Black Matt + Gold

IP20

IC rated

Interior

Output: 475^a, 635^b lm

CIE flux code: 87 98 100 100 100

LED

2700 K

CRI ≥ 90

L80 / 55000h

2 SDCM

OPTICAL

Medium , Beam angle 33°

ELECTRICAL

excl. driver

17 V

LED Inset 6.0^a to 8.7^b W

Class 3

350 to 500 mA

PHYSICAL

Diameter 135 mm

Height 96 mm

0.45 kg

blade springs

CUTOUT


Diameter 127 mm

Min. ceiling thickness 4 mm


Recessed depth 75 mm

^a 350mA

^b 500mA



Round ceiling recessed downlight made from die-cast aluminium; adjustable; surface Black Matt + Gold; wet painted, matt smooth; inner ring black; installation without tools using blade springs; suitable for ceiling thickness of min. 4 mm; recessed depth 75 mm; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; beam angle 33°; 355° rotatable and 60° tiltable; degree of protection IP20; PC3; IC rated; driver not included; light source replaceable by an authorized professional;






WEVER & DUCRÉ
LIGHTING

BLIEK ROUND 1.0 LED

125361K3C

LIGHT DISTRIBUTION



CONE DIAGRAM

medium 33° 500mA

h (m)	EO° (lx)	ø (m)
1	1300	0.60
2	330	1.20
3	140	1.80
4	80	2.41
5	50	3.01

medium 33° 350mA

h (m)	EO° (lx)	ø (m)
1	977	0.60
2	244	1.20
3	109	1.80
4	61	2.41
5	39	3.01

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.96	0.92	0.88	0.85	0.81
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

ELECTRICAL

Driver

TYPE	L · W · H (MM)	VOLTAGE	ORDERCODE
10W 500mA 11-20V	100·43·23	11-20V	9 0 2 1 4 4 0 5
10W 500mA	65·39·20	13-20V	9 0 2 1 4 4 0 6
10W 500mA 3-20V phase-cut dim	102·49·29	3-20V	9 0 2 2 4 4 0 2
10W 500mA	115·41·25	12-21V	9 0 2 2 4 4 0 3
20W 500mA 3-40V DALI	116·40.5·22	3-40V	9 0 2 4 4 6 0 4
24W 500mA	143·43·30	6-49V	9 0 2 4 4 7 0 1