



PROJECT

---

TYPE

---

NOTES

---

QUANTITY

---

DATE


---



IP65



Rectangular wall surface luminaire made from aluminium; surface Black Matt; powder coated; matt texture; RAL 9011; up or down light emission; beam angle 5°x55°; PCB 3-step binning; light colour 3000 K; ≤ 3 SDCM (initial MacAdam); CRI ≥ 80; 220 - 240 V; driver included; degree of protection IP65; Class I; light source not replaceable; control gear replaceable by end-user;



**LUMINAIRE**

Wall  
 Surface  
 Black Matt  
 RAL 9011<sup>a</sup>  
 IP65  
 Exterior  
 170 lm

**LED Module**

3000 K  
 CRI ≥ 80  
 L80 / 60000h  
 ≤ 3 SDCM (initial MacAdam)

**Optical**

Asymetric  
 beam angle 5°x55°  
 CIE flux code: 63 87 97 100 99

**Electrical**

incl. driver  
 220 - 240 V  
 system 5.4 W  
 Class I  
 Standard

**Physical**


length 48 mm  
 width 48 mm  
 height 96 mm  
 0.24 kg

**datasheet.quicksum.material**

Aluminium

<sup>a</sup> Colour may deviate slightly due to production conditions

**LIGHT DISTRIBUTION**



[718143B4] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.