

ODREY WALL 2.3

387420GW0

Project

Type

Notes

Quantity

Date

GENERAL

Wall , Surface

Gold + White Matt

IP20

Interior

Indirect 505^a to 550^b lm

Direct 505^a to 550^b lm

Total 1010^a to 1100^b lm

CIE flux code: 94 98 100 50 91

LED

Lamp PAR16

Socket GU10

max. per socket 12.0 W

CRI ≥ 90

ELECTRICAL

100 - 240 V

LED Inset 13.0 W

Class I

PHYSICAL


Diameter 100 mm

Height 254 mm


0.41 kg

^a PAR16 LAMP 2700K CRI90


^b PAR16 LAMP 3000K CRI90



Wall surface luminaire made from die-cast aluminium; surface Gold + White Matt wet painted; matt texture; up and down light emission; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; degree of protection IP20; PC1; lamp not included;



LIGHT DISTRIBUTION



ODREY
WALL 2.3

387420GW0

LAMPS

PAR16 LED Lamp

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
2700K >90 CRI GU10	Black	ø50 · 60	9 0 1 2 2 8 B 3
3000K >90 CRI GU10	Black	ø50 · 60	9 0 1 2 2 8 B 5
2700K >90 CRI GU10	White	ø50 · 60	9 0 1 2 2 8 W 3
3000K >90 CRI GU10	White	ø50 · 60	9 0 1 2 2 8 W 5
2700K >80 CRI GU10	Silver	ø50 · 60	9 0 5 2 2 7 S 2
3000K >80 CRI GU10	Silver	ø50 · 60	9 0 5 2 2 7 S 4